

MasterPel[®] 777

Robust 2-in-1 High Performance, Water Reducing and Water Proofing Concrete / Mortar Admixture

DESCRIPTION

MasterPel 777 is an innovative liquid admixture designed specifically to allow superior workability in concrete / mortar mixes with reduced water and also achieve high resistance to water ingress. It is based on a specially formulated polymers and compatible with all types of cement and binders (like fly ash, ground granulated slag, silica fume, metakaolin, etc).

RECOMMENDED USES

MasterPel 777 can be used in all types of concrete and mortar that is used in all types of residential, commercial and infrastructural construction. Additionally, it can be used in concrete applications constantly or intermittently in contact with water such as sea walls, tunnels, basements, structural and pre-cast concrete in exposed superstructures.

MasterPel 777 is used as a dual action admixture combining both the waterproofing cum plasticizing effect for cement concrete, mortars and plasters.

FEATURES AND BENEFITS

- Liquid – easy to use.
- Low dosage – Economical.
- Water reducing admixture - Improves workability, cohesion and pump ability, reduces segregation.
- Improved surface finish.
- Improved compressive strengths
- Water proofing admixture - Provides resistance to water penetration either under hydrostatic pressure or capillary absorption.
- Increased durability.

PERFORMANCE TEST DATA

Aspect	Dark Brown liquid
Specific gravity	1.05 ± 0.02 at 25°C
pH	≥6
Chloride ion content	<0.2%

Surface Absorption of water, BS 1881 – Part 122	50% lower than control
---	------------------------

TEST CERTIFICATION/APPROVALS

- IS:2645-2003
- IS:9103-1999
- ASTM C494: Types A & D

DOSAGE

As a guide, a dosage range of 100 ml to 200 ml per 50kg of cementitious material is recommended.

Optimum dosage of **MasterPel 777** should be determined with trial mixes. Higher dosages may be required when certain combinations of materials and conditions are present or water reduction in excess of 15% is required. Because of variations in concrete materials, job site conditions, and/or applications, dosages outside of the recommended range may be required. In such cases, contact your local BASF representative.

For addition information on **MasterPel 777** admixture or on its use in developing concrete mixes with special performance characteristics, contact your local BASF representative.

Points to remember when producing waterproof concrete:

- Ensure W/C ratio is in the range of 0.40 to 0.60.
- Keep water content as low as possible.
- Place concrete quickly and compact it well.
- Ensure complete curing with a MASTERKURE

Effects of over dosage

A severe over-dosage of **MasterPel 777** shall result in some of the followings:

- Extension of initial and final set
- Increase in air entrainment
- Bleed/segregation of mix, quick loss of workability



We create chemistry

MasterPel[®] 777

- Increased plastic shrinkage

A slight overdosing may not adversely affect the ultimate strength of the concrete and can achieve higher strengths than normal concrete, provided it is properly compacted and cured. Due allowance should be made for the effect of fluid concrete pressure on form work, and stripping times should be monitored.

In the event of over dosage, contact your local BASF representative immediately.

APPLICATION

MasterPel 777 is a ready-to-use liquid which is dispensed into the concrete together with the mixing water. The plasticizing effect and water reduction are higher if the admixture is added to the damp concrete after 50 to 70% of the mixing water has been added. The addition of **MasterPel 777** to dry aggregate or cement is not recommended

SUGGESTED SPECIFICATION

The liquid integral water proofer shall be **MasterPel 777**, polymer based, waterproofing cum plasticizing admixture. The product shall comply with IS: 9103 and IS: 2645-2003 when tested at a dosage of 100 ml – 200 ml / 50 Kg bag of cement. The product must be free of chlorides and shall have specific gravity not less than 1.05 and shall comply with ASTM C494 Type A & D.

COMPATIBILITY

MasterPel 777 is compatible with most admixtures used in the production of quality concrete including

normal, other mid-range and high-range water-reducing admixtures, air entrainers, accelerators, retarders, extended set-control admixtures, corrosion inhibitors, and shrinkage reducers.

MasterPel 777 is also compatible with slag and pozzolans such as fly ash and silica fume.

CORROSIVITY – NON CHLORIDE , NON CORROSIVE

MasterPel 777 admixture will neither initiate nor promote corrosion of reinforcing steel embedded in concrete, prestressed concrete or concrete placed on galvanized steel floor and roof systems. Neither calcium chloride nor any calcium chloride-based ingredients are used in the manufacture of **MasterPel 777** admixture. In all concrete application, **MasterPel 777** admixture will conform to the most stringent or minimum chloride ion limits currently suggested by construction industry standards and practices.

WORKABILITY

MasterPel 777 ensures that concrete remains workable in excess of 60 minutes at +25°C. Workability loss is dependent on temperature, and on the type of cement, the nature of aggregates, the method of transport and initial workability.

It is strongly recommended that concrete should be properly cured particularly in hot, windy and dry climates.

PACKAGING

MasterPel 777 is available in 1litre, 5litre, 20litre & 210 litre drums or Bulk.

STORAGE /SHELF LIFE

STATEMENT OF RESPONSIBILITY (Disclaimer)

The technical information and application advice given in this BASF Construction Chemicals publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

® = registered trademark of BASF group in many countries

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by BASF Construction Chemicals either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not BASF Construction Chemicals, are responsible for carrying out procedures appropriate to a specific application.

BASF India Limited
Construction Chemicals Division

Plot.No.12,TTC Area
Thane Belapur Road,Turbhe
Navi Mumbai - 400705,India
Tel: +91 22 6712 7600, Fax: +91 22 67917358
e-mail: construction-india@basf.com , www.master-builders-solutions.basf.in





We create chemistry

MasterPel[®] 777

MasterPel 777 must be stored where temperatures do not drop below +5°C. If product has frozen, thaw at +5°C or above and completely reconstitute using mild mechanical agitation. Do not use pressurized air for agitation. Store under cover, out of direct sunlight and protect from extremes of temperature.

Shelf life is 12 months when stored as above.

Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging. For specific storage advice consult your local BASF representative.

As with all chemical products, care should be taken during use and storage to avoid contact with eyes, mouth, skin and foodstuffs (which can also be tainted with vapour until product fully cured or dried). Treat splashes to eyes and skin immediately. If accidentally ingested, seek immediate medical attention. Keep away from children and animals. Reseal containers after use. Do not reuse containers for storage of consumable item. For further information refer to the material safety data sheet. MSDS available on demand or on BASF construction chemicals web site.

TDS Ref. no.: MasterPel777/01/0515

PRECAUTIONS

STATEMENT OF RESPONSIBILITY (Disclaimer)

The technical information and application advice given in this BASF Construction Chemicals publication are based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use.

® = registered trademark of BASF group in many countries

NOTE

Field service where provided does not constitute supervisory responsibility. Suggestions made by BASF Construction Chemicals either orally or in writing may be followed, modified or rejected by the owner, engineer or contractor since they, and not BASF Construction Chemicals, are responsible for carrying out procedures appropriate to a specific application.

BASF India Limited
Construction Chemicals Division
Plot.No.12,TTC Area
Thane Belapur Road,Turbhe
Navi Mumbai - 400705,India
Tel: +91 22 6712 7600, Fax: +91 22 67917358
e-mail: construction-india@basf.com , www.master-builders-solutions.basf.in

